AMENDMENTS TO THE CLAIMS

1.   (Previously Presented) A method comprising:

determining a power state of a first system, the power state to be one of at least a

first and second power states, the second power state to consume less

power than the first power state; and

in response to the system being in the second power state, switching, without

using a main operating system. a parallel Advanced Technology

Attachment (PATA) link from the first system to a link with an

autonomous subsystem.

2.   (Previously Presented) The method of claim 1, wherein the power state comprises

an Advanced Configuration Power Interface Specification (ACPI) state.

3.   (Canceled)·

4.   (Canceled)

5.   (Previously Presented) The method of claim 2, wherein if the ACPI state is S0,

S1, or S2 then the PATA is switched to the first system, and if the ACPI state is

S3, S4, or S5 then the PATA is switched to the subsystem.

6.   (Previously Presented) The method of claim 2, wherein if the ACPI state is S0, or

S1 then the PATA is switched to the first system, and if the ACPI state is S2, S3,

S4, or S5 then the PATA is switched to the subsystem.

Docket No.: 42P9736   2
Application No.: 09/752,062

7.   (Previously Presented) A machine-readable medium having stored thereon data

representing sets of instructions which, when executed by a machine, cause the

machine to:

determine a power state of a first system, the power state to be at least one of a

    first and second power states, the second power state to consume less

    power than the first power state; and

in response to the system being in the second power state, switch, without using a

    main operating system, a parallel Advanced Technology Attachment

    (PATA) link from the first system to a link with an autonomous

    subsystem.

8.   (Canceled)

9.   (Previously Presented) A system comprising:

a memory;

a Parallel Advance Technology Attachment (PATA) device connected to the

    memory and to a switch; and

the switch to

    connect the system to the PATA device when the system is in a first power

        state, and

    connect an autonomous subsystem to the PATA device, without using a

        main operating system, when the system is in a second power state,

        the second power state to consume less power than the first power

        state.

Docket No.: 42P9736   3
Application No.: 09/752,062

10.   (Previously Presented) The system of claim 9, wherein the switch connecting the

PATA device alternately connects the system and the subsystem to the PATA

device.

11.   (Previously Presented) The system of claim 9, wherein the switch operation is

controlled by signals from the system.

12-15. (Cancelled)

16.   (Previously Presented) The machine-readable medium of claim 7, wherein the

power state comprises an Advanced Configuration Power Interface Specification

(ACPI) state.

17.   (Previously Presented) The machine-readable medium of claim 16, wherein if the

ACPI state is S0, S1, or S2 then the PATA is switched to the first system, and if

the ACPI state is S3, S4, or S5 then the PATA is switched to the subsystem.

18.   (Previously Presented) The machine-readable medium of claim 16, wherein if the

ACPI state is S0, or S1 then the PATA is switched to the first system, and if the

ACPI state is S2, S3, S4, or S5 then the PATA is switched to the subsystem.

Docket No.: 42P9736   4
Application No.: 09/752,062

19. (Previously Presented) An apparatus comprising:

a Parallel Advanced Technology Attachment (PATA) device connected to a

switch; and

the switch to

connect the system to the PATA device when the system is in a first power

state, and

connect an autonomous subsystem to the PATA device, without using a

main operating system, when the system is in a second power state,

the second power state to consume less power than the first power

state.

20. (Previously Presented) The apparatus of claim 19, wherein the switch connecting

the PATA device only connects to either the system or the subsystem.

21. (Previously Presented) The apparatus of claim 19, wherein the switch operation

is controlled by signals from the system.